




MAXHUB Touch Controller

Model: TCP10M

Transform your meeting spaces with the MAXHUB TCP10M touch controller, designed to seamlessly control MAXHUB IFP/Commercial Display/VideoBar family with leading video conferencing solutions. With one-touch join and easy content sharing, you can enhance collaboration and elevate your meeting experience. Plus, with a simple setup using a single cable routed through the back of the device, installation is a breeze.



 High Resolution 10.1" 1920(H)×1080(V)	 Touch Screen 10-point capacitive touch recognition	 Power Over Ethernet A single cable carries both power and data to reduce clutter
 Cable Free Paring Connect to your Maxhub Display /Videobar wirelessly	 Sleek Design Control options are clear and accessible	 Compatibility Compatible with MAXHUB IFP/Commercial Display/VideoBar S10Pro/S15 family

Display	
Size	10.1 inch
Resolution	1920 (H) x 1080 (V)
Refreshing Frequency	60Hz
NTSC	55%
Back Light Unit	ELED
Brightness with glass (typ)	280cd/m²
Life Span	15000 Hours

Operating System	
System Version	Android 10.0
RAM	4G
ROM	16G
CPU	A53×4
GPU	Mali-G52

Touch System	
Sensing Type	Capacitive touch recognition
Touch Tool	Finger,Passive infrared pen (Optional)
Accuracy	±2mm
Touch Point	10 points touch
Minimum Size	6mm

Microphone (For pairing with host only)	
Quantity	2
Distance	0~4m

Bluetooth	
Version	5.0
Working Frequency	2.4GHz
Working Distance	0~10m

Wi-Fi	
Version	802.11a/b/g/n/ac
Working Frequency	2.4GHz;5GHz
Working Distance	0~10m

Power	
Power Requirements	12V3A(Adapter) / 48V0.53A(POE)
Overall Power(Max.)	24W
Standby Power	≤0.5W

I/O Port	
USB 2.0	1
RJ45 IN	1
RJ45 OUT	1
DC2.0	1

Physical Specifications	
Dimension L×H×D	241.6×157.4×83.2mm
Dimension (package) L×W×H	320×225×145mm
Net Weight	0.85kg
Gross Weight	1.86kg

Speaker	
Channel	1.0
Power	1x0.8W

Accessories (included in the package)	
RJ45 cable (5m)	
Adapter (12V/3A)	

Environmental Conditions	
Operation Temperature	0℃~40℃
Operation Humidity	10%~90%RH
Storage Temperature	-20℃~60℃
Storage Humidity	10%~90%RH
Altitude	Below 5000 meters

Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with thelatest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.