

ERE

Quick Installation Guide




For Mac OS X

1 Connect to a Computer

Option 1: Directly





2 Install Driver and Utility

a. Insert the CD.

You can also download the driver and utility at http://www.tp-link.com.


- Browse the CD, go to Archer T4U > Mac OS X Driver, unzip the Mac OS X version.zip file and run the Installer.
- c. Follow the wizard to complete the installation.



3 Join a Wireless Network


Option 1: Via TP-LINK Utility

- a. Click (TP-LINK Wireless Configuration Utility) on the menu bar.
- b. Select your Wi-Fi network and enter the Wi-Fi password when prompted.



Option 2: Via Wi-Fi Protected Setup (WPS)

- a. Press the WPS button on your router.
- b. Within 2 minutes, press and hold the WPS button on the adapter until the configuring screen appears.




 c. When you are prompted "WPS Protocol Finished", click OK.




Connect to a Computer

Option 1: Directly







2 Install Driver and Utility

a. Insert the CD and run the **Autorun.exe** from the pop-up Autoplay window.

Notes:

- 1. You can also download the driver and utility at http://www.tp-link.com.
- 2. In some operating systems, the CD screen will pop up automatically. Otherwise, run the CD manually.
- b. Select **Archer T4U** and click **Install Driver**, then follow the InstallShield Wizard to complete the installation.

Note:

During the installation, select TP-LINK Wireless Configuration Utility and Driver if you want to use TP-LINK Utility and WPS function.



Join a Wireless Network

Option 1: Via Windows Wireless Utility


Click ar or (Network icon) on the taskbar, select your Wi-Fi network, and click **Connect**.

In Windows XP, if you have installed TP-LINK Utility, you need to switch to Windows wireless configuration tool first.



Option 2: Via TP-LINK Utility

Select your Wi-Fi network from the pop-up utility window and click **Connect**. The symbol **1** indicates a successful connection.



TP-LINK_X

Option 3: Via Wi-Fi Protected Setup (WPS)


- a. Press the WPS button on your router.
- b. Within 2 minutes, press and hold the WPS button on the adapter until the configuring screen appears.



c. When you are prompted "Successfully connected to the network by WPS!", click **OK**.



For more information, please visit our website http://www.tp-link.com ©2016 TP-LINK



For Windows

In Windows XP, a Found New Hardware Wizard window will appear when the adapter is detected. Please click Cancel.